AMAZONE

Safe in winter...





The new E+S single disc spreaders are designed for versatile use:
Not only for winter de-icing, fertilising and applying sand to golf courses and sports grounds but also in road construction.




One for all

Precise and reliable

AMAZONE E+S single disc spreaders, with a choice of either PTO shaft drive (540 R.P.M.) or with a hydraulic motor, ensures a versatile use, in winter for spreading salt or salt/sand mixtures and then in spring for spreading mineral fertilisers up to a working width of 8 m.

Plus, of course, all year round use in any season for applying a sand top-dressing on grassed areas of sports grounds and golf courses or for spreading grit during road construction.



Accurate spreading to either side, on pavements and cycle paths, by simply swivelling the spread fan.



The E+S bottom shutter assembly is made from non-corrosive steel and is provided with a manual or – for even more comfortable operation – a hydraulic actuation to open and close the outlet openings. The working width is set either manually, or as an option, electrically for infinite variation.

The E+S metering system allows the patented removal and refitting of all shutter components without tools and without the necessity to unbolt or bolt the hopper. In this way extremely fast, easy cleaning and maintenance is ensured.

Bolt-on hopper extensions for the E+S spreader allow the capacity to be increased to suit individual needs (see technical data).

TECHNICAL DATA:

Machine type	Hopper- capacity	Payload	Empty- weight	Filling height	Filling width	Length	Total width
	(litres)	(kg)	(kg)	(m)	(m)	(m)	(m)
E + S 300	300	1300	160	1,00	0,98	0,90	1,08
E + S 300 + S 130	430	1300	178	1,14	0,95	0,95	1,13
E + S 300 + 2 x S 130	560	1300	196	1,28	0,95	0,95	1,13
E + S 750	750	1300	195	1,30	1,40	1,23	1,50
E + S 750 + S 250	1000	1300	221	1,44	1,37	1,28	1,55

Technical data subject to change. The illustrations also show the special optional equipment.

- Patents and patents applied for -

AMAZONE municipal and landscape gardening (GaLaBau) machinery



ZA-XW Perfect, 500l twin disc fertiliser spreader



Groundkeeper with rear discharge hopper emptying



Groundkeeper with high-lift hopper discharge



Profihopper



Hard court conditioner



Grass re-seeding combination

AMAZONEN-WERKE H. DREYER GmbH & Co. KG · P. O. Box 51 · D-49202 Hasbergen-Gaste/Germany Tel. +49 (0)5405 501-0 · Fax +49 (0)5405 501-193