



AMAZONE

www.precision-today.de

UF – A world of precision

Mounted sprayer | 900 l – 2,000 l | 12 m – 30 m
Extension to 1,000 l or 1,500 l with FT front tank

» Perfect boom ride

The booms in an aircraft wing design are both super-light and super-stable. The free-hanging boom suspension with multiple damping and spring mounting provides an extremely steady boom ride.

» DUS pressure circulation system

The DUS pressure circulation system provides a uniform spray agent concentration.

» Automatic boom guidance

Perfect adherence to the desired distance between the nozzle and the area to be sprayed thanks to the DistanceControl plus automatic boom guidance system with 4 sensors.

» Automatic 50 cm part-width section

Precise switching at the headland and in wedge shaped fields by combining the GPS-Switch automatic part-width section control and the AmaSwitch single nozzle control.

» A reduction in the use of plant protective agents of approx. 5 to 10% depending on the conditions

» SmartCenter operator station for the UF 02 mounted sprayer

The complete operation of the machine is simple, central and logically structured

- The optional **Comfort-Pack** with TwinTerminal enables remotely controlled and automated activation of the spray agent circuit. This includes the automatic filling stop, automatic agitator switch-off, reliable residue draining without foaming and automatic cleaning at the end – very simple and effective.
- The high-performance 60 l **induction bowl** with a suction capacity of 150 l/min guarantees the induction of plant protection agents and micro-nutrients.

AmaTron 4
ISOBUS terminal



GO for Innovation | amazone.net

