



AMAZONE

www.precision-today.de

UX – A world of precision

Trailed sprayer | 3,200 l – 11,200 l | 15 m – 40 m

» Automatic boom guidance

The precise guidance of the boom with the DistanceControl automatic boom guidance system can be further increased for very wide booms and hilly terrain by means of the active ContourControl boom guidance system in conjunction with SwingStop active vibration damping.

» Perfect boom ride

The booms in an aircraft wing design are both super-light and super-stable. The free-hanging boom suspension with multiple damping and spring mounting provides an extremely steady boom ride.

» DUS pressure circulation system

The DUS pressure circulation system provides a uniform spray agent concentration.

» Axle pivot steering with AutoTrail

For precise tracking of the tractor – even in hilly terrain.

» Automatic 50 cm part-width section

Precise switching at the headland and in wedge shaped fields by combining the GPS-Switch automatic part-width section control and the AmaSwitch or AmaSelect single nozzle control.

» A reduction in the use of plant protective agents of approx. 5 to 10% depending on the conditions

» SmartCenter operator station



Standard-Pack

Operation is mainly provided via a suction valve and a pressure valve in the Standard-Pack.



Comfort-Pack

A TwinTerminal 3.0 is also used as standard in the Comfort-Pack. In addition to this, an automatic fill stop is offered for the suction filling.



Comfort-Pack plus

Operation can be made even easier via the large 7" touch screen in the Comfort-Pack plus. In this case, only the function needs to be selected to actuate the respective valves automatically.

AmaTron 4
ISOBUS terminal



GO for Innovation | amazone.net

