



AMAZONE

www.precision-today.net

UX 11201 – A world of precision

Trailed sprayer | 11,200 l | 24 m – 42 m

» Perfect boom ride

The booms in an aircraft wing design are both super-light and super-stable. The free-hanging boom suspension with multiple damping and spring mounting provides an extremely steady boom ride.

» Automatic boom guidance

The precise guidance of the boom with the DistanceControl automatic boom guidance system can be further increased for very wide booms and hilly terrain by means of the active ContourControl boom guidance system in conjunction with SwingStop active vibration damping.

» DUS pressure circulation system

The DUS pressure circulation system provides a uniform spray agent concentration.

» Tandem chassis

The hydro-pneumatic chassis of the UX 11201 Super provides perfect driving comfort and ensures maximum area coverage.

» Automatic 50 cm part-width section

Precise switching at the headland and in wedge shaped fields by combining the GPS-Switch automatic part-width section control and the AmaSwitch or AmaSelect single nozzle control.

» A reduction in the use of plant protective agents of approx. 5 to 10 % depending on the conditions

» SmartCenter operator station with Comfort-Pack

A TwinTerminal 3.0 is used as standard in the Comfort-Pack. In addition to this, an automatic fill stop is offered for the suction filling.

Additional benefits:

- Auto-dynamic agitation control
- Automatic cleaning programme



See more



AmaTron 4 ISOBUS terminal



GO for Innovation | amazone.net

