

Micro plus micro-granular applicator

For rapid seedling development of the plant



The Micro plus hopper can be easily accessed via the loading board



Filling is quick and simple

Micro plus micro-granular applicator

The Micro plus micro-granular applicator can be used to place small quantities of fertiliser directly by the seed corn during sowing. The micro-granular applicator meters the fertiliser into the seed row of the drill. The fertiliser is thereby delivered to the soil via the conveying system together with the seed using a single-shoot process.

Micro plus is equipped with a central electric metering system under the easily-accessible 110 l hopper. The exchangeable metering cassettes in the metering unit can be used for high-output sowing at various application rates.

The filling opening with a diameter of 195 mm enables quick and easy filling. The micro-granular applicator is controlled via the ISOBUS software of the seed drill.

Technical data:

AD-P Special harrow-mounted seed drill

	AD-P 3001 Special	AD-P 3501 Special	AD-P 4001 Special
Working width (m)	3.00	3.50	4.00
Transport width (m)	3.00	3.50	4.00
Number of rows	24/20	28/24	32/26
Row spacing (cm)	12.5/15.00	12.5/14.60	12.5/15.40
Hopper capacity without extension (l)	850/1,250		
Hopper capacity with extension (l)	1,100/1,500		
Height to the upper edge of the seed hopper (m)	1.97/2.12		
Height to the upper edge of the seed hopper with extension (m)	2.07/2.23		
Weight with WS coulters without soil tillage implement (kg)	700 ¹ /715 ²	–	810 ¹ /830 ²
Weight with RoTeC coulters without soil tillage implement (kg)	810 ¹ /825 ²	885 ¹ /900 ²	955 ¹ /975 ²
Weight with KE Super/WS coulters/PW 600 (kg)	2,336 ¹ /2,351 ²	2,573 ¹ /2,588 ²	2,814 ¹ /2,834 ²
Weight with KE Super/WS coulters/KW 580 (kg)	2,341 ¹ /2,356 ²	2,555 ¹ /2,570 ²	2,808 ¹ /2,828 ²
Weight with KE02/RoTeC coulters/PW 600 (kg)	2,447 ¹ /2,367 ²	–	2,807 ¹ /2,822 ²
Weight with KE02/RoTeC coulters/KW 580 (kg)	2,357 ¹ /2,367 ²	–	2,796 ¹ /2,813 ²
Weight with KG Special/RoTeC coulters/PW 600 (kg)	2,666 ¹ /2,681 ²	2,930 ¹ /2,945 ²	3,209 ¹ /3,229 ²
Weight with KG Special/RoTeC coulters/KW 580 (kg)	2,671 ¹ /2,686 ²	2,912 ¹ /2,927 ²	3,203 ¹ /3,223 ²

¹Weight of basic machine 850 l with coulters, blower fan, 12.5 cm row spacing, Exact harrow, bout markers, operator terminal

²Weight of basic machine 1,250 l with coulters, blower fan, 12.5 cm row spacing, Exact harrow, bout markers, operator terminal



Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor have to be checked. Not all the listed combination options are possible with all tractor manufacturers.