Tyres for Pantera 7004

Dimensions	Pantera	Pantera-W	Load index	Outer diameter in mm
380/90 R54	Х	Х	171 D	2054
380/90 R54	Х	Х	176 D	2050
420/95 R50	х	Х	177 D	2052
480/80 R50	Х	х	166 D	2050
480/80 R50	Х	Х	179 D	2050
520/85 R46	х	х	170 D	2052
620/70 R42	х		166 D	1935
650/65 R42	Х		170 D	1940
650/65 R42	х		165 D	1936

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required.



Technical data 94

Technical data: Pantera 7004





Model	Pantera 7004	Pantera 7004-W	
Nominal volume (I) / Actual volume (I)	6,600 / 7,000		
Fresh water tank (I)	500		
Working width (m)	24 –	24 – 48	
Delivery capacity pump (l/min)	610		
Max. suction capacity (I/min)	750	750	
Fuel tank capacity (I)	290 / 400		
DEF tank (I)	20		
Max. working speed (km/h)	20 (30 optional)		
Transport speed (km/h)	up to 50		
Length (m) (Transport position, incl. external wash down kit)	9.77		
Transport width (m)	2.55	2.75	
Spraying height min./max. (m) with tyre sizes 380/90 R50	0.35 – 2.75 with lift module 0.35 – 3.45		
Part-width sections min./max. (number)	7 – 13		
No. of sections with individual nozzle switching: AmaSwitch or AmaSelect	up to 96		
Unladen weight (kg)	approx. 12.000 kg depending on the level of equipment		
Max. total weight (kg)	20,000		
Turning circle, all-wheel steer (m)	4.50		
Track width (m) with tyre sizes 380/90 R50 (offset depth + 50 mm)	2.00 – 2.75	2.25 – 3.00	
Ground clearance (m) with tyre sizes 380/90 R50	1.30		
Engine power	max. 225 kW (306 hp)		

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required.