



Technical data: Cayena trailed tine seeder

	Cayena 6001	Cayena 6001-C
Working width (m)	6.00	6.00
Transport width (m)	3.00	3.00
Coulters	TineTeC or TineTeC HD	
Row spacing	16.6 cm	
Number of seed rows	36	
Seed hopper capacity (l)	3,600	4,000 (divided 60:40)
Operational speed (km/h)	8–15	
Power requirement from (kW/hp)	100/136	
Linkage system	Cat. 3/4N or K700	
Transport running gear	4 integrated transport wheels in the wedge ring roller	
Number of wedge ring tyres	12	
Following harrow	Exact S following harrow	
Weight from (kg)	5,900	6,100
No. of spool valves required	2 double acting + 1 single acting + pressure-free return flow	

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.



AMAZONEN-WERKE H. DREYER SE & Co. KG
P. O. Box 51 · 49202 Hasbergen-Gaste/Germany
Phone +49 (0)5405 501-0 · Fax +49 (0)5405 501-193