



Cenio mounted cultivator		Cenio 3000 Special/Super	Cenio 3500 Special/Super	Cenio 4000-2 Special/Super
Working width (m)		3.00	3.50	4.00
Execution		rigid		folding
Transport width (m)		3.00	3.50	3.00
Transport length with road lights (m)		3.60		4.80
Weight (kg) (Base machine, simplest execution)	Special	1,325	1,445	2,585
	Super	1,515	1,675	2,895
Linkage		3-point linkage mounted (Cat. 3/3N)		
No. of tines		10	12	13
Tine execution	Special	C-Mix Special tines with shear bolt overload safety protection		
	Super	C-Mix Super tines with pressure spring overload protection		
Number of stagger		3		
Tine spacing: tine element (cm)		30		
Frame height (cm)		75		
Working depth: tine element (cm)		5–30		
Operational speed (km/h)		8–15		
Power requirement from (kW/hp)		75/105	90/125	130/175
No. of d/a tractor spool valves		0/1		2

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.



AMAZONEN-WERKE H. DREYER SE & Co. KG

P. O. Box 51 · 49202 Hasbergen-Gaste/Germany

Phone +49 (0)5405 501-0 · Fax +49 (0)5405 501-193