

| Model | Precea 3000 | Precea 3000-FCC | Precea 3000-A | Precea 3000-AFCC | Precea 3300 |
|---|---|--------------------|--------------------------|--|--|
| Equipment option | Special/Super | Super | Super | Super | Special/Super |
| Frame execution | rigid | rigid | Harrow-mounted seeder | Harrow-mounted air seeder + mounted front hopper | rigid |
| Working width (m) | 2.70–3.20 | | 3.00 | | 3.80 |
| Number of sowing units | 4, 5, 6 | | 4, 5, 6 | | 5, 7 |
| Possible row spacing (cm) | 45, 50, 60, 65, 70, 75, 80 | | 50, 60, 75 | 50, 60, 70, 75 | 50, 70, 75 |
| Transport width (m) on 75 cm row spacing | 3.00 | | 3.00 | | 3.30 |
| Transport length from (m) | 2.00 | | 3.05 | | 2.00 |
| Singling drive | Special mechanical / Super electric | electric | | | Special mechanical / Super electric |
| Drive: fertiliser metering | Special mechanical / Super electric | electric | | | Special mechanical / Super electric |
| Operational speed (km/h) | Special 3–12/ Super 3–15 | up to 15 | 3–15 | 3–12 | Special 3–12/ Super 3–15 |
| Seed spacing | 3.1 cm to 86.9 cm depending on the singling disc used | | | | |
| Singling unit | Singling discs for maize, sunflowers, sugar beet, rape, soya, sorghum, field beans, peas | | | | |
| Fertiliser hopper capacity (l) | 950/1,250 | | 950 | 1600/2200 | 950/1,250 |
| Seed hopper capacity (l) | 55/70 | | | | |

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.

Technical data: Precea precision air seeder

| Model | Precea 4500 | Precea 4500-2 | | | Precea 4500-2FCC | | |
|---|---|--------------------------|-------------------|-----------|-----------------------|-------------------|-----------|
| Equipment option | Special/Super | Special/Super | | | Super | | |
| Frame execution | rigid | single | double | variable* | single | double | variable* |
| Working width (m) | 3.50–4.80 | 3.60–4.80 | 4.20–4.80 | 2.70–4.80 | 3.60–4.80 | 4.20–4.80 | 2.70–4.80 |
| Number of sowing units | 5, 6, 7, 8 | 6, 7 | | | | | |
| Possible row spacing (cm) | 45, 50, 60, 65, 70, 75, 80 | 60, 65, 70, 75, 80 | 60, 70, 75, 80 | 45–80 | 60, 65, 70, 75, 80 | 60, 70, 75, 80 | 45–80 |
| Transport width (m) on 75 cm row spacing | 4.50 | 3.30 | 3.00 | | 3.30 | 3.00 | |
| Transport length from (m) | 2.00 | | | 2.30 | 2.00 | | 2.30 |
| Singling drive | Special mechanical / Super electric | | | | electric | | |
| Drive: fertiliser metering | Special mechanical / Super electric | | | | electric | | |
| Operational speed (km/h) | Special 3–12/Super 3–15 | | | | 3–15 | | |
| Seed spacing | 3.1 cm to 86.9 cm depending on the singling disc used | | | | | | |
| Singling unit | Singling discs for maize, sunflowers, sugar beet, rape, soya, sorghum, field beans, peas | | | | | | |
| Fertiliser hopper capacity (l) | 950/1,250 | 950/1,250 or 1,600/2,000 | | | | | |
| Seed hopper capacity (l) | 55/70 | | | | | | |

* Only available as Super version

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.



| Model | Precea 6000 | Precea 6000-2 | Precea 6000-2CC | Precea 6000-2FCC | Precea 6000-2AFCC |
|--|---|----------------------------|-----------------|----------------------------|--|
| Equipment option | Special/Super | Special/Super | Special/Super | Super | Super |
| Frame execution | rigid | folding | | | folding |
| Working width (m) | 5.40–6.20 | 5.40–6.80 | | | 6.00 |
| Number of sowing units | 8, 9, 12 | 8, 9, 12 | 8, 9 | 8, 9, 12 | 8 |
| Possible row spacing (cm) | 45, 50, 60, 65, 70, 75, 80 | 45, 50, 60, 65, 70, 75, 80 | 60, 70, 75, 80 | 45, 50, 60, 65, 70, 75, 80 | 75 |
| Transport width (m) on 75 cm row spacing | 6.20 | 3.00 | | | 3.30 m mechanical coulter pressure/3.00 m hydraulic coulter pressure |
| Transport length from (m) | 2.00 | | 2.50 | 2.00 + FTender | 3.25 |
| Singling drive | Special mechanical / Super electric | | | electric | |
| Drive: fertiliser metering | Special mechanical / Super electric | | | electric | |
| Operational speed (km/h) | Special 3–12 / Super 3–15 | | | 3–15 | 3–12 |
| Seed spacing | 3.1 cm to 86.9 cm depending on the singling disc used | | | | |
| Singling unit | Singling discs for maize, sunflowers, sugar beet, rape, soya, sorghum, field beans, peas | | | | |
| Fertiliser hopper capacity (l) | 950 / 1,250 | – | 950 / 1,250 | 1,600 / 2,200 | 1,600 / 2,200 |
| Seed hopper capacity (l) | 55 / 70 | | | | 55 |

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.